

DEEP CYCLE 36VM60

38.4V / 60AH / 2304WH



PRO-GUIDE®

UNIT SPECIFICATIONS

Nominal Voltage	38.4V
Nominal Capacity	60Ah
Stored Energy	2304Wh
Protection Level	IP67
Standard Discharge Current	12A
Continuous Discharge Current	60A
Discharge Cut off Voltage	30V
Charge Cut off Voltage	43.2V
Standard Charge Current	10-12A
Max Continuous Charge Current	30A
Self Discharge	1-3% Per Month
Cycle Life	>3000 times @ 100% DOD >6000 times @ 80% DOD

TEMPERATURE SPECIFICATIONS

Operating Temperature	
Charging Temperature	-4F-131F (-20C-55C)
Discharging Temperature	-4F-140F (-20C-60C)
Storage Temperature	
3 Months	23F-113F (-5C-45C)
1 Year	23F-113F (-5C-45C)


SLEEP SPECIFICATIONS

Sleep Timer	Will not enter sleep mode until it reaches 10-20% or is turned off manually
Heating	Enabled
Bluetooth	Enabled
NMEA 2000	Compatible

The Pro-Guide PGL36VM60 is engineered specifically for electric trolling motors and deep-cycle marine use. Featuring a 60 amp-hour capacity (2304 watt-hours), robust 100-amp BMS, IP67 waterproof rating, and Bluetooth connectivity, this battery ensures consistent performance. The Pro-Boost mode reserves 10% capacity, ensuring power remains steady even under demanding conditions.

MEASUREMENTS

Weight 41.89 lbs



PRO-GUIDE®

PRO-GUIDE LITHIUM BATTERY SPECIFICATIONS



PRO-GUIDE Part #	Industry Group Size	Nom V	AH	Rated WH	PbEq CCA	Charge Amp		Terminal Type	Gross Wt		Dimension (mm)			Dimension (in)		
						STD	MAX		kg	lb	L	W	H	L	W	H
PRO-GUIDE LITHIUM DUAL PURPOSE																
31M180-DP	Group 31	12.8	180	2304	1000	10	90	3 Internal Tread (M8)	19	41.89	332	176	226	13.07	6.93	8.9
31M235-DP	Group 31 Tall	12.8	235	3008	1000	10	117.5	3 Internal Tread (M8)	24	52.91	332	176	275	13.07	6.93	10.83
PRO-GUIDE LITHIUM DEEP CYCLE																
16VM160	Group 31 Tall	16	160	2560	N/A	10	80	3 Internal Tread (M8)	20	44.09	332	176	275	13.07	6.93	10.83
24VM90	Group 31	25.6	90	2304	N/A	10	45	3 Internal Tread (M8)	19	41.89	332	176	226	13.07	6.93	8.9
24VM115	Group 31 Tall	25.6	115	2944	N/A	10	57.5	3 Internal Tread (M8)	24	52.91	332	176	275	13.07	6.93	10.83
36VM60	Group 31	38.4	60	2304	N/A	10	30	3 Internal Tread (M8)	20	44.09	332	176	226	13.07	6.93	8.9
36VM75	Group 31 Tall	38.4	75	2880	N/A	10	37.5	3 Internal Tread (M8)	23	50.71	332	176	275	13.07	6.93	10.83